

UniPak 129 x 129 mm 1150 ml

Product no: 5624

Shape: Square
 Available lids: 2520 (Standard)



VOLUME

Volume under lid:	1150 ml	Volume brimful:	1250 ml
--------------------------	---------	------------------------	---------

DIMENSIONS

Length top:	128.5 mm	Width top:	128.5 mm
Length bottom:	105.9 mm	Width bottom:	105.9 mm
Height:	108.6 mm		

WEIGHT

Weight:	33.5 g ± 3 g	Weight plastic handle:	4 g ± 0.4 g
----------------	--------------	-------------------------------	-------------

PERFORMANCE

Stacking tests: The stacking tests have been performed with the standard raw material as stated above at 23° C over a period of 2 months. Stackability depends on many factors and the above data is meant as an indication only. Consequently, customers should make internal trials to determine the viability of stacking and transportation.

Special: Tolerances for length and width: -0/+1 mm

CLOSURE SYSTEM	HANDLE
-----------------------	---------------

Lid type options:	Standard	Standard handle:	Flexible plastic hanging
Closure type:	Snap-On		
Protective collar:	Yes		
Tamper Evidence type:	Tamper Evidence tab		

DECORATION

Decoration available:	IML
------------------------------	-----

RAW MATERIAL

Raw material options:	PP	Hot filling:	85-95° C
Masterbatch colours:	Colours according to RPC Superfos standard selected pantone colours.		

Hot temperatures:
 The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging become flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling. The RPC Superfos packaging must be tested by the customer with the actual product before approval for use at hot temperatures.

Cold temperatures:
 Freezing conditions require special resins available on request.
 The RPC Superfos packaging must be tested by the customer with the actual product before approval for use at low temperatures.

QUALITY SPECIFICATIONS

Approvals: All RPC Superfos Products comply with the European Union Commission Regulation No. 10/2011/EC with amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use.

Shelf life: The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very low temperatures or very high temperatures over a long period.

Quality information: Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the Standard Sales and Delivery Terms in force at the time of delivery.